

- Industry 4.0 adopted Display Unit with computerized MICS system with 3,5" color Touchscreen
- Up to 4 Probes connection or 4 WIRELESS connections
- **Functions:** Go/NoGo, Max/Min, Formula, Timer, Linear correction, Temperature correction, Resolution selecting, Connection status
- **Memory manager:** 2000 values, Folders system, Statistics mode, Memory data transfer
- **4 MODES DATA TRANSFER:** WIRELESS to MDS app (Windows, Android, iOS, MacOS); WIRELESS HID, WIRELESS HID+MAC, USB HID
- Calibration certificate included (ISO17025 (Iac MRA))



0,1µm



Item No	INPUT CONNECTION			Data output			Memory	Display	Battery	Footswitch
	INDUCTIVE PROBES	CAPACITIVE PROBES	WIRELESS	MODBUS	WIRELESS	USB				
299999010	1	-	max 4	option	Wireless to MDS, Wireless HID Wireless HID+MAC	USB HID	Folders 2000 vol Statistics	Touch 3.5"	Recharge Li-Pol	option
299999012	2	-								
299999014	4	-								
299999024	-	4								



CAPACITIVE LINEAR PROBES

Item No	Range		Resol.	Accu- racy	Hyste- resis	Force	Cable lenght	Clamping	Output socket
	mm	inch							
120129137P	0-13	0-0.5"	0,0001	±2	0,5	0,6-1	2	Ø 8-h6	7 pin
120129258P	0-25	0-1"		±2		0,7-1.2			
120129508P	0-50	0-2"		±3	1,2-2,2	Optional 10			
120129907P	0-100	0-4"		±5	3,2-5,2				
120129507P	0-150	0-6"		±7					



INFORMATION FOR REQUEST

INDUCTIVE LINEAR PROBES