

DIGITAL THICKNESS GAUGES

- Different type of contact points and gauges configuraiton for customer requirement
- Digital indicator with 1 or 10 micron resolution
- Functions: Go/NoGo, MIN/MAX, Preset, mm/inch conversion
- Calibration certificate included (ISO17025 (Ilac MRA))



Item No	Range		Depth	Resolution		Accuracy	Contact points		Calibration
	mm	inch		mm	mm		inch	µm	
137001021	0-1	0-0,04"	25	0,001	0,0005"	±0,003	Flat d 10mm	Flat d 12, 16, 20, 25, 30mm	+
137010122	0-10	0-0,4"	120	0,01	0,005"	±0,020			+
137010121			200	0,001	0,0005"	±0,012			+
137010202			0,01	0,005"	±0,025	+			
137010201	0-20	0-0,8"	200	0,001	0,0005"	±0,015			+
137020122			120	0,01	0,005"	±0,025			+
137020121			200	0,001	0,0005"	±0,015			+
137025202	0-25	0-1"	200	0,01	0,005"	±0,030			+
137025201			400	0,001	0,0005"	±0,018			+
137025402			0,01	0,005"	±0,040	+			
137025401			0,001	0,0005"	±0,025	+			
137050102	0-50	0-2"	100	0,01	0,005"	±0,030			+
137050101			200	0,001	0,0005"	±0,015			+
137050202			0,01	0,005"	±0,040	+			
137050201			0,001	0,0005"	±0,020	+			
137050302			300	0,01	0,005"	±0,040			+
137050301			400	0,001	0,0005"	±0,025			+
137050402			0,01	0,005"	±0,050	+			
137050401			0,001	0,0005"	±0,030	+			
137050602			600	0,01	0,005"	±0,060			+
137050601			0,001	0,0005"	±0,035	+			
137100102	0-100	0-4"	100	0,01	0,005"	±0,030			+
137100101			200	0,001	0,0005"	±0,015			+
137100202			0,01	0,005"	±0,040	+			
137100201			0,001	0,0005"	±0,020	+			
137100402			400	0,01	0,005"	±0,050			+
137100401			0,001	0,0005"	±0,030	+			
137100502			600	0,01	0,005"	±0,060			+
137100501			0,001	0,0005"	±0,040	+			

