

DIAL INDICATOR CALIBRATION COMPUTERIZED STAND WIRELESS

0.1µm

RESOLUTION



WIRELESS
DATA TRANSFER



TOLERANCE FUNCTION



MEMORY MANAGER



FORMULA MODE



TEMPERATURE
COMPENSATION



ERROR COMPENSATION



RECHARGEABLE
BATTERY

- Patent UA99686, UA103982, UA126928, UA131637, UA99931, W02016124992 by MICROTECH
- Universal calibration stands for indicators and bore gauges calibration
- **INTELLIGENT** computerized indication system **MICS** with colour touchscreen display adapted to Industry 4.0
- Functions: Go/NoGo, Max/Min, Memory, Statistic, Timer, Formula, mm/inch, Preset, Calibration date, Lock, Mathematical & Temperature error compensation, Switch off, Brightness, Rotation, Rechargeable Li-Pol battery
- **Wireless** data transfer to Windows, Android, iOS applications with distance up to **50 m**
- **FREE** version of software for Windows PC, Android, iOS tablets and smartphones
- Calibration certificate included (ISO17025 (Ilac MRA))



Free Software for Windows, Android, iOS

max 50 m
data transfer distance



Item No	Range		Resolution		Micrometer head		Calibration devices	Indication	Data output	Calibration
	mm	inch	mm	inch	Range	Accuracy				
25111026	0-25	0-1"	0,0001	0,00001"	25	±0,002	Dial indicators	computerized MICS system with 1,54" touchscreen	Wireless	ISO17025
25111051	0-50	0-2"			50	±0,003			max 50 m	+
									max 50 m	+



MICROTECH

since 1995



www.microtech.ua



ISO 17025



ISO 9001:2015