



DIGITAL BORE GAUGE


- Solid construction with depth up to 2000mm Measuring range up to 1500mm
- Modifications with Digital indicators with 1 or 10 micron resolution
- Functions: Go/NoGo, Max/Min, Preset, mm/inch
- Calibration certificate included (ISO17025 (Ilac MRA))



6-10 mm



10-18 mm
18-50 mm



over 50 mm



DIGITAL BORE GAUGE

Item No	Range		Resolution		Depth	Accuracy	Calibration	Item No	Range		Resolution		Depth	Accuracy	Calibration
	mm	inch	mm	inch					mm	inch	mm	inch			
131010300	6-10	0.24-0.4"	0,01	0,005"	45	±8	+	131010800	6-10	0.24-0.4"	0,001	0,0005"	45	±3	+
131018300	10-18	0.4-0.7"			45	±8	+	131018800	10-18	0.4-0.7"			45	±3	+
131050300	18-50	0,7-2"			135	±12	+	131050800	18-50	0,7-2"			135	±3	+
131050311					500	±12	+	131050811					500	±3	+
131050322					1000	±12	+	131050822					1000	±3	+
131050344					2000	±12	+	131050844					2000	±3	+
131160300					200	±15	+	131160800					200	±3	+
131160311	50-160	2-6,5"			500	±15	+	131160811	50-160	2-6,5"			500	±3	+
131160322					1000	±15	+	131160822					1000	±3	+
131160344					2000	±15	+	131160844					2000	±3	+
131250300					200	±15	+	131250800					200	±5	+
131250311	160-250	6,5-10"			500	±15	+	131250811	160-250	6,5-10"			500	±5	+
131250322					1000	±15	+	131250822					1000	±5	+
131250344					2000	±15	+	131250844					2000	±5	+
131450300	250-450	10-18"			200	±22	+	131450800	250-450	10-18"			200	±8	+
131450311					500	±22	+	131450811					500	±8	+
131450322					1000	±22	+	131450822					1000	±8	+
131450344					2000	±22	+	131450844					2000	±8	+
131800300	400-800	16-32"			250	±30	+	131800800	400-800	16-32"			250	±8	+
131800311					500	±30	+	131800811					500	±9	+
131800322			1000	±30	+	131800822	1000	±9			+				
131800344			2000	±30	+	131800844	2000	±9			+				
131900300	700-1000	28-40"	400	±30	+	131900800	700-1000	28-40"	400	±12	+				
131900322			1000	±30	+	131900822			1000	±12	+				
131900344			2000	±30	+	131900844			2000	±12	+				

WIDE RANGE MICRON DIGITAL BORE GAUGE

Item No	Range		Resolution		Depth	Accuracy	Calibration
	mm	inch	mm	inch			
131110800	10-100	0,4-4"	0,001	0,0005"	45	±3	+
131220800	20-200	0,8-8"			200	±3	+
131224800	50-250	2-10"			200	±3	+
131225800	18-250	0,7-10"			150	±3	+
131951800	130-1500	5-60"			500	±8	+

WIDE RANGE DIGITAL BORE GAUGE

Item No	Range		Resolution		Depth	Accuracy	Calibration
	mm	inch	mm	inch			
131110300	10-100	0,4-4"	0,01	0,005"	45	±15	+
131220300	20-200	0,8-8"			200	±15	+
131224300	50-250	2-10"			200	±15	+
131225300	18-250	0,7-10"			150	±20	+
131951300	130-1500	5-60"			500	±25	+

