

SUB-MICRON COMPUTERIZED BORE GAUGE WIRELESS



- Patent UA 99686, UA126928, UA131637, WO2016124990 by MICROTECH
- Solid construction with depth up to 2000mm
- Resolution **0,1 μ m**
- **INTELLIGENT** computerized indication system **MICS** with colour touchscreen display adapted to Industry 4.0
- Functions: Go/NoGo, Max/Min, Memory, Statistic, Timer, Formula, mm/inch, Preset, Calibration date, Lock, Mathematical & Temperature error compensation, Switch off, Brightness, Rotation, Rechargeable Li-Pol battery
- **Wireless** data transfer to Windows, Android, iOS applications with distance up to **50 m**
- **FREE** version of software for Windows PC, Android, iOS tablets and smartphones
- Calibration certificate included (ISO17025 (Ilac MRA))




SUB-MICRON COMPUTERIZED BORE GAUGE WIRELESS


	Range		Resolution		Depth	Accuracy	Indication	Data output	Calibration		
	mm	inch	mm	inch	mm	µm		Wireless			
131010700	6-10	0.24-0.4"	0,0001	0,00001"	45	±3	computerized MICS system with 1,54" touchscreen	50m	+		
131017300	10-18	0.4-0.7"			45	±3		50m	+		
131050700	18-50	0,7-2"			135	±3		50m	+		
131050711					500	±3		50m	+		
131050722					1000	±3		50m	+		
131050744					2000	±3		50m	+		
131160700					50-160	2-6,5"		200	±3	50m	+
131160711								500	±3	50m	+
131160722	1000	±3						50m	+		
131160744	2000	±3						50m	+		
131250700	160-250	6,5-10"			200	±5		50m	+		
131250711					500	±5		50m	+		
131250722					1000	±5		50m	+		
131250744					2000	±5		50m	+		
131450700	250-450	10-18"			200	±8		50m	+		
131450711					500	±8		50m	+		
131450722					1000	±8		50m	+		
131450744					2000	±8		50m	+		
131800700	400-800	16-32"			250	±8		50m	+		
131800711					500	±9		50m	+		
131800722					1000	±9		50m	+		
131800744					2000	±9		50m	+		
131900700	700-1000	28-40"			400	±12		50m	+		
131900722					1000	±12		50m	+		
131900744					2000	±12		50m	+		

WIDE RANGE COMPUTERIZED BORE GAUGE WIRELESS


	Range		Resolution		Depth	Accuracy	Indication	Data output	Calibration
	mm	inch	mm	inch	mm	µm		Wireless	
131110700	10-100	0,4-4"	0,0001	0,00001"	45	±3	computerized MICS system with 1,54" touchscreen	50m	+
131220700	20-200	0,8-8"			200	±3		50m	+
131224700	50-250	2-10"			200	±3		50m	+
131225700	18-250	0,7-10"			150	±3		50m	+
131951700	130-1500	5-60"			500	±8		50m	+



6-10 mm



10-18 mm
18-50 mm



over 50 mm

