

- Industry 4.0 adopted height gauge with computerized MICS system
- Touchscreen operating on 2,4" full color display (320x240px)
- Ergonomic navigation menu with quick access to all functions
- Modifications with E-Force control module with Force selection 1-20N, color indication, autosaving data when requested Force reached
- Memory for 2000 values with Folders system and Statistics
- Built-in Wireless long range data transfer with singal strenght regulation (range up to 100m depends on area conditions)
- USB HID data transfer to any Windows, Linux, Android, macOS app with no special software in keyboard mode
- Free software for Windows PC and Android, iOS Smartphones
- Rechargeable internal Li-Pol battery throw USB socket
- Completion: micrometer, USB magnetic cable, manual, calibration protocol (ISO17025 accredited lab), plastic box.

FEATURES



FORCE CONTROL
1-20N
FORCE SELECTION
INDICATION: GREEN-OK RED-NO
AUTO DATA SAVING MODE

USB HID CONNECTION
macOS Windows Android
KEYBOARD MODE LINUX

FREE SOFTWARE
Windows iOS Android

MENU 1.5337 0	MENU Stat All 1: 0.0000 2: 1.2334 3: 1.2337 4: 1.2333 5: 1.2341	Display Angle 180 Sleep 15s	MENU -1.7210 0	MENU 7.2241 0	Formula AX+BX+C Set Argv	Timer +000 sec. RESET	Calibration DAY MONTH YEAR 01 01 2020 CHANGE
COLOR DISPLAY Resolution X.0000 Millimeters	MEMORY 2000 VAL.	FOLDERS SYSTEM	MEMORY EXPORT	STATISTIC	TEMP. COMPENSATION Glass, Quartz Solid alloys, Mo	LINEAR CORRECTION	FIRMWARE UPDATE

MADE IN EUROPE

Item No	Range		Resolution	Accuracy	Fine adjust.	Preset	Go/NoGo	Max/Min	Formula	Timer	Temp comp	Linear corr	Calibr date	Rotating disp	Energy saving	Menu	Recharge batt	PIN lock	Values	Folders	Statistic	Wireless	Wireless HID	USB HID	Color Display	Touchscreen	
	mm	inch	mm	µm															Memory	Data							
1443030260	0-300	0-12"	0,01	±40	•	•	•	•	•	•	•	•	•	•	•	•	•	•	2000	•	•	•	-	•	2.4"	•	
1443050260	0-500	0-20"	0,01	±50	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	-	•		•	•
1443100260	0-1000	0-40"	0,01	±70	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	-	•		•	•
1443150260	0-1500	0-60"	0,01	±90	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	-	•		•	•
1443200260	0-2000	0-80"	0,01	±110	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	-	•		•	•

TABLET FORCE HEIGHT GAUGE

Item No	Range		Resolution	Accuracy	eForce control	Preset	Go/NoGo	Max/Min	Formula	Timer	Temp comp	Linear corr	Calibr date	Rotating disp	Energy saving	Menu	Recharge batt	PIN lock	Values	Folders	Statistic	Wireless	Wireless HID	USB HID	Color Display	Touchscreen		
	mm	inch	mm	µm	N														Memory	Data								
1443030262	0-300	0-12"	0,01	±30	1-20N	•	•	•	•	•	•	•	•	•	•	•	•	•	2000	•	•	•	-	•	2.4"	•		
1443030261			0,001	±20		•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	•	•		-	•	•
1443050262	0-500	0-20"	0,01	±40		•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	•	-		•	•	•
1443050261			0,001	±30		•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	•	•		-	•	•
1443100262	0-1000	0-40"	0,01	±50		•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	•	-		•	•	•
1443100261			0,001	±40		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	-	•	•	•	
1443150262	0-1500	0-60"	0,01	±70		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	-	•	•	•		
1443150261			0,001	±60		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	-	•	•	•	
1443200262	0-2000	0-80"	0,01	±90		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	-	•	•	•		
1443200261			0,001	±75		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	-	•	•	•	

OPTIONAL ACCESORIES



DOWNLOAD APP



MADE IN EUROPE