



Item No	Range		Resolution	Accuracy	Micrometer head range	Setting rod
	mm	inch				
110174001	300-400	12-15"	0,001	±7	25	+
110175001	400-500	15-20"		±7	25	+
110176001	500-600	20-24"		±8	25	+
110177001	600-700	24-28"		±8	25	+
110178001	700-800	28-32"		±15	25	+
110179001	800-900	32-36"		±15	25	+
110171101	900-1000	36-40"		±15	25	+
110171201	1000-1200	40-48"		±18	50	+
110171401	1200-1400	48-56"		±20	50	+
110171601	1400-1600	56-64"		±25	50	+
110171801	1600-1800	64-72"		±30	50	+
110172001	1800-2000	72-80"		±35	50	+
110172201	2000-2200	80-88"		±40	50	+
110172401	2200-2400	88-96"		±45	50	+
110172601	2400-2600	96-104"		±50	50	+
110172801	2600-2800	104-112"		±55	50	+
110173001	2800-3000	112-120"		±60	50	+

OPTIONAL ACCESORIES

STANDARD MDS data set



STANDARD MDS app

FUNCTIONS

- LIMITS (Go/NoGo)
- PEAK VALUES (MAX/MIN)
- MEMORY, WITH STATISTICS
- TIMER
- FORMULA AX^2+BX+C
- MM/INCH
- PRESET
- CALIBRATION DATE CONTROL
- PIN LOCK

- LINEAR CORRECTION
- TEMPERATURE COMPENSATION
- RECHARGEABLE LI-POL BATTERY
- MAGNETIC CHARGING SOCKET

WIRELESS APPS FOR WINDOWS, ANDROID, iOS
DATA TRANSFER TO MDS

USB HID DATA TRANSFER DIRECT TO WINDOWS,
MACOS, ANDROID, LINUX APP'S