



WIRELESS TO MDS APP  
WIRELESS HID+MAC  
USB HID

Windows Android LINUX macOS iOS

Item No	Range		Reso- lution	Accu- racy	Depth	Anvils type	Travel	Preset	Go/NoGo	Max/Min	Formula	Timer	Temp comp	Linear corr	Calibr date	Recharge batt	Memory	Wireless	USB	
	mm	inch																		mm
1150500507	0-50	0-2"	0,0001	±3	18	D 8mm	3	•	•	•	•	•	•	•	•	•	Folders / 2000 val	Long range / HID	USB HID	
1150501007	50-100	2-4"		±4	32			•	•	•	•	•	•	•	•	•				•
1150501507	100-150	4-6"		±4	62			•	•	•	•	•	•	•	•	•				•
1150502007	150-200	6-8"		±4	85			•	•	•	•	•	•	•	•	•				•
1150502507	200-250	8-10"		±6	110			•	•	•	•	•	•	•	•	•				•
1150503007	250-300	10-12"		±7	110			•	•	•	•	•	•	•	•	•				•
1150503507	300-350	12-14"		±8	110			•	•	•	•	•	•	•	•	•				•
1150504007	350-400	14-16"		±9	110			•	•	•	•	•	•	•	•	•				•
1150504507	400-450	16-18"		±10	110			•	•	•	•	•	•	•	•	•				•
1150505007	450-500	18-20"		±10	110			•	•	•	•	•	•	•	•	•				•
COMPUTERIZED DISK SNAP GAUGE																				
1150500517	0-50	0-2"	0,0001	±4	18	D 35mm	3	•	•	•	•	•	•	•	•	•	Folders / 2000 val	Long range / HID	USB HID	
1150501017	50-100	2-4"		±4	32			•	•	•	•	•	•	•	•	•				
1150501517	100-150	4-6"		±6	62			•	•	•	•	•	•	•	•	•				
1150502017	150-200	6-8"		±7	85			•	•	•	•	•	•	•	•	•				
COMPUTERIZED UNIVERSAL SNAP GAUGE																				
1150500577	0-40	0-2"	0,0001	±4	18	7 pairs inter- change	3	•	•	•	•	•	•	•	•	•	Folders / 2000 val	Long range / HID	USB HID	
1150501077	40-90	2-4"		±4	32			•	•	•	•	•	•	•	•	•				
1150501577	90-140	4-6"		±6	62			•	•	•	•	•	•	•	•	•				
1150502077	140-100	6-8"		±7	85			•	•	•	•	•	•	•	•	•				



D 35MM

