



Item No	Radius		Resolution	Accuracy	Base	Display	Data output
	Range	Type					
	mm	inch	μm	%	mm		
1250511008	5-1000	0,2-40"	1	1	10, 20, 30, 60, 100	Color 1.5" Touch-screen	WIRELESS+USB
1250511307	225-5500	9-220"		>2500mm -1% 225-2500mm -0,3%	300		
1250511507	625-15600	25-625"		>5000mm -1% 625-5000mm -0,3%	500		

OPTIONAL ACCESORIES



- ITEM 299110100 EXTERNAL MICRO POWERBANK 1000MAH
- ITEM 299110200 EXTERNAL SLIM POWERBAN 5000MAH
- ITEM 299110500 EXTERNAL PRI POWERBANK 20000MAH

FUNCTIONS

- LIMITS (Go/NoGo)
- PEAK VALUES (Max/Min)
- MEMORY, WITH STATISTICS
- TIMER
- FORMULA aX^2+bX+c
- MM/INCH
- PRESET
- CALIBRATION DATE CONTROL
- PIN LOCK

- LINEAR CORRECTION
- TEMPERATURE COMPENSATION
- RECHARGEABLE LI-POL BATTERY
- MAGNETIC CHARGING SOCKET

- WIRELESS** APPS FOR WINDOWS, ANDROID, iOS DATA TRANSFER TO MDS
- USB** HID DATA TRANSFER DIRECT TO WINDOWS, MacOS, ANDROID, LINUX app's