



Item No	Radius		Type	Resolution µm	Base length mm	Accuracy %	Display	Data output
	Range	mm						
1250530256	60-2550	2.5-100"	external	1	600	0,05%	Color 1.5" Touch-screen	WIRELESS+USB
1250531156	100-11200	4-450"			1200	0,05%		
1250533356	200-32200	8-1290"			2000	0,05%		



OPTIONAL ACCESORIES



- Item 299110100 EXTERNAL MICRO POWERBANK 1000MAH
- Item 299110200 EXTERNAL SLIM POWERBAN 5000MAH
- Item 299110500 EXTERNAL PRI POWERBANK 20000MAH

FUNCTIONS

- LIMITS (Go/NoGo)
- PEAK VALUES (Max/Min)
- MEMORY, WITH STATISTICS
- TIMER
- FORMULA AX^2+BX+C
- MM/INCH
- PRESET
- CALIBRATION DATE CONTROL
- PIN LOCK

- LINEAR CORRECTION
- TEMPERATURE COMPENSATION
- RECHARGEABLE LI-POL BATTERY
- MAGNETIC CHARGING SOCKET

- WIRELESS** APPS FOR WINDOWS, ANDROID, iOS
DATA TRANSFER TO MDS
- USB** HID DATA TRANSFER DIRECT TO WINDOWS,
MACOS, ANDROID, LINUX APP'S