



| Item No  | Range  |       | Resolution | Micrometer head |          | Calibration devices       | Display                    | Data output  |
|----------|--------|-------|------------|-----------------|----------|---------------------------|----------------------------|--------------|
|          | mm     | inch  |            | Range           | Accuracy |                           |                            |              |
| 25111300 | 0-300  | 0-12" | 0,0001     | 25              | ±2       | Bore gauges<br>Indicators | Color 1.5"<br>Touch-screen | WIRELESS+USB |
| 25111500 | 0-500  | 0-20" |            |                 |          |                           |                            |              |
| 25111900 | 0-1000 | 0-40" |            |                 |          |                           |                            |              |

OPTIONAL ACCESSORIES



- ITEM 299110100 EXTERNAL MICRO POWERBANK 1000MAH
- ITEM 299110200 EXTERNAL SLIM POWERBAN 5000MAH
- ITEM 299110500 EXTERNAL PRI POWERBANK 20000MAH

FUNCTIONS

- LIMITS (Go/NoGo)
- PEAK VALUES (Max/Min)
- MEMORY, WITH STATISTICS
- TIMER
- FORMULA AX<sup>2</sup>+BX+C
- MM/INCH
- PRESET
- CALIBRATION DATE CONTROL
- PIN LOCK

- LINEAR CORRECTION
- TEMPERATURE COMPENSATION
- RECHARGEABLE LI-POL BATTERY
- MAGNETIC CHARGING SOCKET

**WIRELESS** APPS FOR WINDOWS, ANDROID, IOS  
DATA TRANSFER TO MDS

**USB** HID DATA TRANSFER DIRECT TO WINDOWS,  
MACOS, ANDROID, LINUX APP'S

