



Item No	Range		Resolution	Jaws	Accuracy	Weight	Display	Data output
	mm	inch	mm	mm	µm	kg		
142405243	0-500	0-20"	0,01	200	±20	2,7	Color 2.4" Touch-screen	WIRELESS+USB
142305243			0,001	200	±20	2,7		
142405343			0,01	300	±30	2,9		
142305343			0,001	300	±25	2,9		
142405443			0,01	400	±30	3,3		
142305443			0,001	400	±25	3,3		
142411243	0-1050	0-42"	0,01	200	±30	3,5		
142311243			0,001	200	±25	3,5		
142411443			0,01	400	±40	3,9		
142311443			0,001	400	±35	3,9		
142415243	0-1500	0-60"	0,01	200	±50	5,2		
142415443				400	±50	5,6		
142115182				800	±85	20		
142120132	0-2000	0-80"		300	±60	10,5		
142120152				500	±85	23		
142120102				1000	±120	26		
142125132	0-2500	0-100"		300	±90	13,3		
142125152				500	±105	26		
142125102				1000	±140	29		
142130132	0-3000	0-120"		300	±100	15,4		
142130152				500	±110	28		
142130102				1000	±160	32		
142135132	0-3500	0-140"		300	±120	17,4		
142135152				500	±160	33		
142135102				1000	±240	37		

OPTIONAL ACCESSORIES



- ITEM 299110100 EXTERNAL MICRO POWERBANK 1000MAH
- ITEM 299110200 EXTERNAL SLIM POWERBAN 5000MAH
- ITEM 299110500 EXTERNAL PRI POWERBANK 20000MAH

FUNCTIONS

- E-FORCE 1-20 N WITH AUTO MODE
- LIMITS (Go/NoGo)
- PEAK VALUES (Max/Min)
- MEMORY, WITH STATISTICS
- TIMER
- FORMULA AX^2+BX+C
- MM/INCH
- PRESET
- CALIBRATION DATE CONTROL
- PIN LOCK

- LINEAR CORRECTION
- TEMPERATURE COMPENSATION
- RECHARGEABLE LI-POL BATTERY
- MAGNETIC CHARGING SOCKET

WIRELESS APPS FOR WINDOWS, ANDROID, iOS
DATA TRANSFER TO MDS

USB HID DATA TRANSFER DIRECT TO WINDOWS,
MACOS, ANDROID, LINUX APP'S