

- Industry 4.0 adopted E-Force caliper with computerized MICS system with 1,54" color Touchscreen
- Patents US10184772, UA174949, UA126928
- Functions: Go/NoGo, Max/Min, Formula, Timer, Linear correction, Temperature correction, Resolution selecting, Connection indication
- Memory manager: 2000 values, Folders system, Statistics mode, Memory data transfer
- E-Force control module with Force selection 1-20N, color indication, AUTO-Force mode, Force indication
- WIRELESS long range data transfer to **Free** MICROTECH SPC app for Windows, Android, iOS
- WIRELESS HID & USB HID data transfer to any Windows, Linux, Android, macOS app like keyboard
- Calibration certificate included (ISO17025 (Ilac MRA))



Item No	Range		Resolution	Accuracy*	eForce	Carbide jaws	Preset	Go/NoGo	Max/Min	Formula	Timer	Temp comp	Linear corr	Calibr date	Connect. status	Recharge batt	Memory	Wireless	USB	Color Display
	mm	inch																		
141097015A	0-150	0-6"	0,001	±5	1-20		•	•	•	•	•	•	•	•	•	•	Folders / 2000 val	Long range / HID	USB HID / Update	Touchscreen 1,54"
141077015A			0,005	±10		•	•	•	•	•	•	•	•	•	•	•				
141077015C			•	•		•	•	•	•	•	•	•	•	•	•	•				
141097020A	0-200	0-8"	0,001	±8	1-20		•	•	•	•	•	•	•	•	•	Folders / 2000 val	Long range / HID	USB HID / Update	Touchscreen 1,54"	
141077020A			0,005	±10		•	•	•	•	•	•	•	•	•	•					
141077020C			•	•		•	•	•	•	•	•	•	•	•	•					•
141097030A	0-300	0-12"	0,001	±10	1-20		•	•	•	•	•	•	•	•	•	Folders / 2000 val	Long range / HID	USB HID / Update	Touchscreen 1,54"	
141077030A			0,005	±15		•	•	•	•	•	•	•	•	•	•					
141077030C			•	•		•	•	•	•	•	•	•	•	•	•					•
NIB JAW COMPUTERIZED CALIPER																				
141077321A	0-300	0-12"	0,005	±15	1-20	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
141097321A			0,001	±12		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•

The screenshots show the following interface elements:

- MENU**: Shows 'GO/NOGO', 'MAX/MIN', '0', and folder icons.
- Stat**: Lists 5 memory values (0.0000 to 1.2341).
- Display**: Shows 'Angle 180', 'Sleep 15s', and a power indicator.
- Resolution**: Shows 'X.0000' and 'Millimeters'.
- Formula**: Shows 'AX+BX+C' and 'Set Argv'.
- Timer**: Shows '+000 sec.' and 'RESET'.
- Temp.comp.**: Shows 'Glass, Quartz, Solid alloys, Mo' and '+00.00'.
- Folders System**: Shows folder icons and '0.8970', '0.8920'.
- Calibration**: Shows 'DAY MONTH YEAR' (01 01 2020) and 'CHANGE'.
- Firmware Update**: Shows a USB icon and a plus sign.

*Accuracy on external jaws. Internal jaws and Depth according ISO13385-1

DOWNLOAD APP

