

- High quality indicator with IP65 proof
- PRESET, mm/inch, HOLD function
- USB data transfer
- CR2032 3V battery
- **Calibration** certificate included (ISO17025 (Ilac MRA))

Item No	Range		Resolution		Accuracy	Force	Proof	mm/inch	Preset	ABS	USB DATA	
	mm	inch	mm	inch	µm	N						
120125131			0,01	0.0005"	±10		IP65	•	•	•	•	
120125132					±6			•	•	•	•	
120125133	0-12,7	0-0,5"	0,001	0.00005"	±4	0.6-1		•	•	•	•	
120125134					±3				•	•	•	•
120125135					±2				•	•	•	•
120125250					0,01	0.0005"		±20		•	•	•
120125251	0-25,4	0-1"			±10	0.7-1.2		•	•	•	•	
120125252				0,001	0.00005"			±6	•	•	•	•
120125253								±4	•	•	•	•
120125500			0,01	0.0005"	±20			•	•	•	•	
120125502	0-50,8	0-2"	0,001	0.00005"	±7	1.2-2.2		•	•	•	•	
120125503								±5			•	•
120125900			0,01	0.0005"	±30			•	•	•	•	
120125901	0-100	0-4"			±20	3-5		•	•	•	•	
120125902				0,001	0.00005"			±12	•	•	•	•
120125904								±8	•	•	•	•
120125951	0-150	0-6"	0,01	0.0005"	±30			•	•	•	•	
120125954				0,001	0.00005"	±10			•	•	•	•



OPTIONAL ACCESSORIES



120125000 USB HID DATA TRANSFER CABLE
DIRECT DATA TRANSFER, LIKE A KEYBOARD

- Top quality dial indicator
- 0.01 or 0.001mm resolution
- Jeweled bearing
- Modification with SHOCKPROOF & WATERPROOF
- With adjustable tolerance markers
- **Calibration** certificate included (ISO17025 (Ilac MRA))



Item No	Range	Resolution	Accuracy	Bezel D	Shockproof	Jeweled	Tol. markers	Waterproof	Rubber sleeve
	mm	mm	µm	mm					
120121010	0-1	0,001	±3	60		•	•		
120121100	0-10	0,01	±15		•	•	•	•	•
120120100						•	•	•	•
120121300	0-30		±25		•	•	•	•	•
120121500	0-50		±35		•	•	•	•	•
120121990	0-100		±40		•	•	•	•	•