

- For inside measurings
- Digital IP65 or Computerized **MICS** indication system Modification with **Long range** Wireless, Wireless HID or USB HID data transfer to Windows, Android, iOS, macOS, Linux systems direct to any app.
- Calibration certificate included (ISO17025 (Ilac MRA))



PAT.US99686

Item No	Range		Reso- lution	Accu- racy	Tube D	Extension rods	Proof	Preset	Go/NoGo	Max/Min	Formula	Timer	Temp comp	Linear corr	Calibr date	Connect status	Recharge batt	Memory	Wireless	USB	Color Display	
	mm	inch																				mm
DIGITAL INSIDE MICROMETER IP65																						
133800102	125-1000	5-40"	0.001	±20	22	25, 50 (2pcs), 100, 200, 400	IP65	•														
133800152	125-1500	5-60"		±25		25, 50 (2pcs), 100 (2pcs), 200, 400 (2pcs)																
133800202	125-2100	5-84"	±30	25, 50 (2pcs), 100 (2pcs), 200 (2pcs), 400 (3pcs)																		
133800302	125-3000	5-120"	±40	25, 50 (2pcs), 100 (2pcs), 200 (3pcs), 400 (5pcs)																		
133800402	125-4000	5-160"	±50	25, 50 (2pcs), 100 (2pcs), 200 (2pcs), 400 (8pcs)																		
SUB-MICRON COMPUTERIZED INSIDE MICROMETER IP65																						
133800100	125-1000	5-40"	0.0001	±15	22	25, 50 (2pcs), 100 (2pcs), 200, 400 (2pcs)	IP65	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
133800150	125-1500	5-60"		±15		25, 50 (2pcs), 100 (2pcs), 200, 400 (2pcs)																
133800200	125-2100	5-84"	0.001	±20	25, 50 (2pcs), 100 (2pcs), 200 (2pcs), 400 (3pcs)																	
133800300	125-3000	5-120"	0.01	±30	25, 50 (2pcs), 100 (2pcs), 200 (3pcs), 400 (5pcs)																	
133800400	125-4000	5-160"	±40	25, 50 (2pcs), 100 (2pcs), 200 (2pcs), 400 (8pcs)																		

- High quality indicator with IP65 proof
- Narrow form for wide installation possibilities
- PRESET, mm/inch, HOLD function
- USB data transfer
- CR2032 3V battery
- Calibration certificate included (ISO17025 (Ilac MRA))

Item No	Range		Resolution		Accuracy	Force	Proof	mm/inch	Preset	ABS	USB DATA
	mm	inch	mm	inch							
120125131			0,01	0.0005"	±10	0.6-1	IP65	•	•	•	•
120125132					±6			•	•	•	•
120125133	0-12,7	0-0.5"	0,001	0.00005"	±4			•	•	•	•
120125134					±3			•	•	•	•
120125135					±2						
120125250			0,01	0.0005"	±20	0.7-1.2	IP65	•	•	•	•
120125251	0-25,4	0-1"			±10			•	•	•	•
120125252			0,001	0.00005"	±6			•	•	•	•
120125253					±4						
120125500			0,01	0.0005"	±20	1.2-2.2	IP65	•	•	•	•
120125502	0-50,8	0-2"	0,001	0.00005"	±7			•	•	•	•
120125503					±5			•	•	•	•
120125900			0,01	0.0005"	±30	3-5	IP65	•	•	•	•
120125901	0-100	0-4"			±20			•	•	•	•
120125902			0,001	0.00005"	±12			•	•	•	•
120125904					±8			•	•	•	•



OPTIONAL ACCESSORIES



120125000 USB HID DATA TRANSFER CABLE
DIRECT DATA TRANSFER, LIKE A KEYBOARD

DIAL INDICATOR SHOCKPROOF, WATERPROOF

- Top quality dial indicator
- High Level SHOCKPROOF & WATERPROOF
- With adjustable tolerance markers
- Calibration certificate included (ISO17025 (Ilac MRA))

Item No	Range		Resolution	Accuracy	Force	Shockproof	Waterproof	Rubber sleeve
	mm	mm						
120120100	0-10		0,01	±15	0.6-1	•	•	•



MIKROKATOR

- Micron MIKROKATOR with 28mm stem
- Classic construction with SHOCKPROOF
- Calibration certificate included (ISO17025 (Ilac MRA))

Item No	Range		Resolution	Accuracy	Force	Stem D	Shockproof
	mm	mm					
120120280	0.03		0,001	±0,3	1.8-2.2	28	•

