

- Industry 4.0 adopted Tablet caliper with computerized MICS system with 2.4" color Touchscreen
- Patents US10184772, UA174949, UA126928
- Functions: On-line Graphic, Analog scale, Go/NoGo, Max/Min, Formula, Timer, Linear correction, Temperature correction
- Measuring HUB: Wireless MICROTECH instrument connection, Synchronization, 2D mode, 2D Graph, Probe mode, Compensation
- Memory manager: 2000 values, Folders system, Statistics mode, Memory data transfer
- E-Force control module with Force selection 1-20N, color indication, AUTO-Force mode, Force indication
- DATA TRANSFER: WIRELESS to MDS app (Windows, Android, iOS, MacOS); WIRELESS HID, WIRELESS HID+MAC; USB HID
- Top quality Aluminium housing (CNC machined solid block)
- Calibration certificate included (ISO17025 (Ilac MRA))

MEASURING HUB
MICROTECH DEVICES CONNECT

WIRELESS TO MDS APP
WIRELESS HID+MAC
USB HID

Windows Android LINUX macOS iOS

133.273

FORCE CONTROL
1-20N

ON-LINE GRAPHIC MODE

14.1936 average:5.7457

DOWNLOAD APP

Download Windows App

Download on the App Store

GET IT ON Google play

Item No	Range		Resol.	Jaws	Accuracy	eForce	Measuring HUB	Analog scale	ON-line Graphic	Preset	Go/NoGo	Max/Min	Formula	Timer	Temp comp	Linear corr	Calibr date	Connect. status	Recharge batt	Memory	Wireless	USB	Color Display		
	mm	inch																						mm	mm
141005216	0-500	0-20"	0,01	100	±30	1-20	●	●	●	●	●	●	●	●	●	●	●	●	●	Folders / 2000 val	Long range / HID	USB HID / Update	Touchscreen 2.4"		
141005226				150	±30		●	●	●	●	●	●	●	●	●	●	●	●	●					●	
141005256				300	±30		●	●	●	●	●	●	●	●	●	●	●	●	●					●	
141006216	0-630	0-25"		100	±30		●	●	●	●	●	●	●	●	●	●	●	●	●					●	
141010216				150	±40		●	●	●	●	●	●	●	●	●	●	●	●	●					●	
141010256	0-1000	0-40"		300	±50		●	●	●	●	●	●	●	●	●	●	●	●	●					●	
141015216				150	±50		●	●	●	●	●	●	●	●	●	●	●	●	●					●	
141015256	0-1500	0-60"		300	±60		●	●	●	●	●	●	●	●	●	●	●	●	●					●	●
141020216				150	±50		●	●	●	●	●	●	●	●	●	●	●	●	●					●	●
141020256	0-2000	0-80"		●	±60		●	●	●	●	●	●	●	●	●	●	●	●	●					●	●
141025256	0-2500	0-100"	●	±80	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●						
141030256	0-3000	0-120"	●	±90	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●						
141040256	0-4000	0-160"	●	±110	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●						
141050256	0-5000	0-200'	●	±130	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●						

- Industry 4.0 adopted Extra long jaw Tablet caliper with computerized MICS system with 2.4" color Touchscreen
- Patents US10184772, UA111194, UA112361, UA121681, UA2022205040
- Functions: On-line Graphic, Analog scale, Go/NoGo, Max/Min, Formula, Timer, Linear correction, Temperature correction
- Measuring HUB: Wireless MICROTECH instrument connection, Synchronization, 2D mode, 2D Graph, Probe mode, Compensation
- Aluminium construction with precision roll sliding system
- Memory manager: 2000 values, Folders system, Statistics mode, Memory data transfer
- 3 MODES DATA TRANSFER: WIRELESS to MDS app (Windows, Android, iOS, MacOS); WIRELESS HID, WIRELESS HID+MAC
- Calibration certificate included (ISO17025 (Ilac MRA))

WIRELESS TO MDS APP
WIRELESS HID+MAC
USB HID

Windows Android LINUX macOS iOS

ROLL SLIDING SYSTEM

- Light aluminium base
- 2x steel roll for easy sliding

ON-LINE GRAPHIC MODE

14.1936 average:5.7457

0-0004 50 points 21

Item No	Range		Resol.	Jaws	Accu- racy	Weight	Measuring HUB	Analog scale	ON-line Graphic	Preset	Go/NoGo	Max/Min	Formula	Timer	Temp comp	Linear corr	Calibr date	Connect. status	Recharge batt	Memory	Wireless	USB	Color Display	
	mm	inch																						mm
142408442	0-800	0-32"	0,01	400	±30	3,9	•	•	•	•	•	•	•	•	•	•	•	•	•	Folders / 2000 val Long range / HID USB HID / Update Touchscreen 2.4"				
142411442	0-1000	0-40'		400	±40	4,3	•	•	•	•	•	•	•	•	•	•	•	•	•					
142411462				600	±60	4,7	•	•	•	•	•	•	•	•	•	•	•	•	•					
142415442	0-1800	0-60"		400	±80	6.2	•	•	•	•	•	•	•	•	•	•	•	•	•					
142415462				600	±100	6,6	•	•	•	•	•	•	•	•	•	•	•	•	•					
142120142	0-2000	0-80"		400	±60	17,5	•	•	•	•	•	•	•	•	•	•	•	•	•					
142120162				600	±85	18,0	•	•	•	•	•	•	•	•	•	•	•	•	•					
142120102				1000	±120	19,0	•	•	•	•	•	•	•	•	•	•	•	•	•					
142125142	0-2500	0-100"		400	±90	20.0	•	•	•	•	•	•	•	•	•	•	•	•	•					•
142125162				600	±105	20,5	•	•	•	•	•	•	•	•	•	•	•	•	•					•
142125102				1000	±140	21.5	•	•	•	•	•	•	•	•	•	•	•	•	•					•
142130142	0-3000	0-120"		400	±100	24.0	•	•	•	•	•	•	•	•	•	•	•	•	•					•
142130162				600	±110	24.5	•	•	•	•	•	•	•	•	•	•	•	•	•					•
142130102				1000	±160	25.5	•	•	•	•	•	•	•	•	•	•	•	•	•					•
142135142	0-3500	0-140"		400	±120	26.5	•	•	•	•	•	•	•	•	•	•	•	•	•					•
142135162				600	±160	27.0	•	•	•	•	•	•	•	•	•	•	•	•	•					•
142135102				1000	±240	28.0	•	•	•	•	•	•	•	•	•	•	•	•	•					•

DOWNLOAD APP

Download Windows App

Download on the App Store

GET IT ON Google play