

- Industry 4.0 adopted sub-micron Computerized indicator with computerized MICS system with 1,54" color Touchscreen
- Up to 4 Probes connection or 4 WIRELESS connections
- **Functions:** Go/NoGo, Max/Min, Formula, Timer, Linear correction, Temperature correction, Resolution selecting, Connection status
- **Memory manager:** 2000 values, Folders system, Statistics mode, Memory data transfer
- **4 MODES DATA TRANSFER:** WIRELESS to MDS app (Windows, Android, iOS, MacOS); WIRELESS HID, WIRELESS HID+MAC, USB HID
- Calibration certificate included (ISO17025 (Ilac MRA))



Item No	INSTRUMENTS CONNECTION		Data output			Memory	Functions	Display	Battery	Footswitch
	INDICATORS	WIRELESS	MODBUS	Wireless	USB					
29999904	max 4	max 4	option	Wireless to MDS, Wireless HID Wireless HID+MAC	USB HID	Folders 2000 vol Statistics Graphic	- Formula - LIMITS (Go/NoGo) - PEAK (Max/Min) - TIMER - Graph, 2D Graph - Analog scale	Touch 3.5"	Recharge Li-Pol	option

MEASURING PROBES

Item No	Range		Resol.	Accu- racy	Hyste- resis	Force	Cable length	Clamping	Output socket
	mm	inch							
120129137P	0-13	0-0.5"	0.0001	±2	0,5	0,6-1	2	Ø 8-h6	7 pin
120129258P	0-25	0-1"		±2		0,7-1.2			
120129508P	0-50	0-2"		±3		1,2-2,2			
120129907P	0-100	0-4"		±5	3.2-5.2				
120129007P	0-150	0-6"		±7					

