

- Industry 4.0 adopted sub-micron Thread micrometer with computerized MICS system with 2.4" color Touchscreen
- Functions: On-line Graphic, Analog scale, Go/NoGo, Max/Min, Formula, Timer, Linear correction, Temperature correction
- Measuring HUB: Wireless MICROTECH instrument connection, Synchronization, 2D mode, 2D Graph, Probe mode, Compensation
- Memory manager: 2000 values, Folders system, Statistics mode, Memory data transfer
- Interchangeable anvils SET includes (Metric 60 or Whitworth 55). Custom anvils for request.
- 4 MODES DATA TRANSFER:** WIRELESS to MDS app (Windows, Android, iOS, MacOS); WIRELESS HID, WIRELESS HID+MAC, USB HID
- Calibration certificate included (ISO17025 (Ilac MRA))

## NON-ROTATING

0,1µm



THREAD ANVILS  
SET & STANDARD  
(over 25m range)  
INCLUDES

Item No	Range		Resol.	Accur.	Anvils SET	Thread standard													
	mm	inch				NON-ROTATING	Analog scale	Graphic	Preset	Go/NoGo	Max/Min	Formula	Timer	Temp corr	Linear corr	Calibr date	Recharge	2D Syncronize	Memory

### THREAD COMPUTERIZED MICROMETERS WITH METRIC 60 ANVILS SET

110710258	0-25	0-1"		±3		0.4-7mm 6pcs															
110710508	25-50	1-2"		±3			•	•	•	•	•	•	•	•	•	•	•	•	•	•	
110710758	50-75	2-3"		±4			•	•	•	•	•	•	•	•	•	•	•	•	•	•	
110711008	75-100	3-4"		±4			•	•	•	•	•	•	•	•	•	•	•	•	•	•	
110711258	100-125	4-5"		±5			•	•	•	•	•	•	•	•	•	•	•	•	•	•	
110711508	125-150	5-6"		±5			•	•	•	•	•	•	•	•	•	•	•	•	•	•	
110711758	150-175	6-7"		±6			•	•	•	•	•	•	•	•	•	•	•	•	•	•	
110712008	175-200	7-8"		±7			•	•	•	•	•	•	•	•	•	•	•	•	•	•	
110712258	200-225	8-9"	0,0001	±7			•	•	•	•	•	•	•	•	•	•	•	•	•	•	
110712508	225-250	9-10"		±8			•	•	•	•	•	•	•	•	•	•	•	•	•	•	
110712758	250-275	10-11"		±8			•	•	•	•	•	•	•	•	•	•	•	•	•	•	
110713008	275-300	11-12"		±8			•	•	•	•	•	•	•	•	•	•	•	•	•	•	
110713258	325-350	12-13"		±9			•	•	•	•	•	•	•	•	•	•	•	•	•	•	
110713508	350-375	13-14"		±9			•	•	•	•	•	•	•	•	•	•	•	•	•	•	
110713758	250-375	14-15"		±10			•	•	•	•	•	•	•	•	•	•	•	•	•	•	
110714008	375-400	15-16"		±10			•	•	•	•	•	•	•	•	•	•	•	•	•	•	

### THREAD COMPUTERIZED MICROMETERS WITH WHITWORTH 55 ANVILS SET

110720258	0-25	0-1"		±3		60-35 TPI 10pcs															
110720508	25-50	1-2"		±3			•	•	•	•	•	•	•	•	•	•	•	•	•	•	
110720758	50-75	2-3"		±4			•	•	•	•	•	•	•	•	•	•	•	•	•	•	
110721008	75-100	3-4"		±4			•	•	•	•	•	•	•	•	•	•	•	•	•	•	
110721258	100-125	4-5"		±5			•	•	•	•	•	•	•	•	•	•	•	•	•	•	
110721508	125-150	5-6"		±5			•	•	•	•	•	•	•	•	•	•	•	•	•	•	
110721758	150-175	6-7"		±6			•	•	•	•	•	•	•	•	•	•	•	•	•	•	
110722008	175-200	7-8"	0,0001	±7			•	•	•	•	•	•	•	•	•	•	•	•	•	•	
110722258	200-225	8-9"		±7			•	•	•	•	•	•	•	•	•	•	•	•	•	•	
110722508	225-250	9-10"		±8			•	•	•	•	•	•	•	•	•	•	•	•	•	•	
110722758	250-275	10-11"		±8			•	•	•	•	•	•	•	•	•	•	•	•	•	•	
110723008	275-300	11-12"		±8			•	•	•	•	•	•	•	•	•	•	•	•	•	•	
110723258	325-350	12-13"		±9			•	•	•	•	•	•	•	•	•	•	•	•	•	•	
110723508	350-375	13-14"		±9			•	•	•	•	•	•	•	•	•	•	•	•	•	•	
110723758	250-375	14-15"		±10			•	•	•	•	•	•	•	•	•	•	•	•	•	•	
110724008	375-400	15-16"		±10			•	•	•	•	•	•	•	•	•	•	•	•	•	•	

## OPTIONAL ACCESSORIES



IOT MDS CONNECT DISPLAY UNIT  
USB, WI-FI, RJ-45, RS-485, LoRa output

## DOWNLOAD APP

