


- Tubular Inside micrometers with range up to 6m
- Digital IP65 or Computerized **MICS** indication system Modification with **Long range** Wireless, Wireless HID or USB HID data transfer to Windows, Android, iOS, macOS, Linux systems direct to any app.
- **Calibration** certificate included (ISO17025 (Ilac MRA))



Item No	Range		Reso- lution	Accu- racy	Tube D	Extension rods	Proof	Preset	Go/NoGo	Max/Min	Formula	Timer	Temp comp	Linear corr	Calibr date	Recharge	Memory	WIRELESS	USB	Display
	mm	inch	mm	μm	mm	mm														
DIGITAL INSIDE MICROMETER IP65																				
133800102	125-1000	5-40"	0,001	±20	22	25, 50 (2pcs), 100, 200, 400	IP65	•												
133800152	125-1500	5-60"		±25		25, 50 (2pcs), 100 (2pcs), 200, 400 (2pcs)		•												
133800202	125-2100	5-84"		±30		25, 50 (2pcs), 100 (2pcs), 200 (2pcs), 400 (3pcs)		•												
133800302	125-3000	5-120"		±40		25, 50 (2pcs), 100 (2pcs), 200 (3pcs), 400 (5pcs)		•												
133800402	125-4000	5-160"		±50		25, 50 (2pcs), 100 (2pcs), 200 (2pcs), 400 (8pcs)		•												
133800502	125-5000	5-200"		±70	33	25, 50 (2pcs), 100 (2pcs), 200 (3pcs), 400 (10pcs)		•												
133800602	125-6000	5-240"		±80		25, 50 (2pcs), 100 (2pcs), 200 (4pcs), 400 (12pcs)		•												
SUB-MICRON COMPUTERIZED TUBULAR INS																				