




- Retractable construction of measuring part for block bores, grooves and recesses
- For the determination of internal diameters, where a smaller bore lying in front of this diameter, has to be passed
- Patents UA147920, UA150454, UA99686
- Digital or Computerized **MICS** indication system Modification with **4 MODES DATA TRANSFER**: WIRELESS to MDS app (Windows, Android, iOS, MacOS); **WIRELESS HID**, **WIRELESS HID+MAC**, **USB HID**
- Calibration certificate included (ISO17025 (Ilac MRA))



DOWNLOAD APP



CUSTOM RANGE AND DEPTH FOR REQUEST

Item No*	Range D	Max A	Min H	MaxH	DIGITAL	COMPUTERIZED																
					resolution	resolution	Preset	Go/NoGo	Max/Min	Formula	Timer	Temp comp	Linear corr	Calibr date	FW update	Recharge	Memory	WIRELESS	USB	Display		
					1 μm *X - 8	0.1 μm *X - 7															Accuracy	Accur.
	mm		mm	μm	μm																	
139160X00	70-160	20	D-30	150	±15	±12	●	●	●	●	●	●	●	●	●	●	Folders / 2000 val	Long range / HID	USB HID / Update firmware	Touchscreen 1,54"		
139160X11				1000	±25	±20	●	●	●	●	●	●	●	●	●	●						
139160X22				2000	±30	±25	●	●	●	●	●	●	●	●	●	●						
139160X33				3000	±35	±30	●	●	●	●	●	●	●	●	●	●						
139250X00	160-250			150	±15	±12	●	●	●	●	●	●	●	●	●	●					●	
139250X11				1000	±25	±20	●	●	●	●	●	●	●	●	●	●						
139250X22				2000	±30	±25	●	●	●	●	●	●	●	●	●	●						
139250X33				3000	±35	±30	●	●	●	●	●	●	●	●	●	●						
139450X00	250-450			150	±15	±12	●	●	●	●	●	●	●	●	●	●					●	●
139450X11				1000	±25	±20	●	●	●	●	●	●	●	●	●	●					●	
139450X22				2000	±30	±25	●	●	●	●	●	●	●	●	●	●					●	
139450X33				3000	±35	±30	●	●	●	●	●	●	●	●	●	●					●	
139550X00	250-550			60	100+0,3*D	380	±25	±20	●	●	●	●	●	●	●	●					●	●
139780X00	480-780	400	±30			±25	●	●	●	●	●	●	●	●	●	●						
139910X00	720-1020	400	±35			±30	●	●	●	●	●	●	●	●	●	●						