


- Industry 4.0 adopted sub-micron Computerized thickness gauge with range up to 150mm and depth up to 800mm
- Functions: Go/NoGo, Max/Min, Formula, Timer, Linear correction, Temperature correction, Resolution selecting, Connection status
- Memory manager: 2000 values, Folders system, Statistics mode, Memory data transfer
- Quick reading system (50 value/sec)
- **4 MODES DATA TRANSFER:** WIRELESS to MDS app (Windows, Android, iOS, MacOS); WIRELESS HID, WIRELESS HID+MAC, USB HID
- Calibration certificate included (ISO17025 (Ilac MRA))



CUSTOM RANGE AND DEPTH FOR REQUEST

Item No	Range	Reso- lution	Accuracy	Depth	Contact points D		Preset	Go/NoGo	Max/Min	Formula	Timer	Temp comp	Linear corr	Calibr date	FW update	Recharge	Memory	WIRELESS	USB	Display	
	mm	mm	µm	mm	Standard mm	Optional mm															
137001027	0-1	0.0001	±3	25	6,35	Flat d 12, 16, 20, 25, 30, 35, 40 Point D 0.3 Blade 0.7	•	•	•	•	•	•	•	•	•	•					
137010127	0-10		±8	120			•	•	•	•	•	•	•	•	•	•	•				
137020127	0-20		±12	120			•	•	•	•	•	•	•	•	•	•	•				
137025207	0-25		±15	200			•	•	•	•	•	•	•	•	•	•	•				
137025407			±20	400			•	•	•	•	•	•	•	•	•	•	•				
137050207	0-50		±18	200			•	•	•	•	•	•	•	•	•	•	•				
137050307			±20	300			•	•	•	•	•	•	•	•	•	•	•				
137050407			±22	400			•	•	•	•	•	•	•	•	•	•	•				
137050607			±30	600			•	•	•	•	•	•	•	•	•	•	•				
137050807	0-100		±35	800			•	•	•	•	•	•	•	•	•	•	•				
137100207			±15	200			•	•	•	•	•	•	•	•	•	•	•				
137100407			±24	400			•	•	•	•	•	•	•	•	•	•	•				
137100607			±32	600			•	•	•	•	•	•	•	•	•	•	•				
137100807	0-150		±44	800			•	•	•	•	•	•	•	•	•	•	•				
137150407			±50	400			•	•	•	•	•	•	•	•	•	•	•				
137150807			±70	800			•	•	•	•	•	•	•	•	•	•	•				
137300407	150-300		±60	400			•	•	•	•	•	•	•	•	•	•	•				
137300807			±85	800			•	•	•	•	•	•	•	•	•	•	•				

OPTIONAL ACCESSORIES



DOWNLOAD APP



CONTACT POINTS

