

- Bore calipers for bore reading without removing the bar
- Digital IP54 electronics with PRESET function.
- **Calibration** certificate included (ISO17025 (Ilac MRA))

Item No	Range				Reso- lution	Accu- racy	Jaws		Preset
	Internal		External				Down	Depth	
	mm	inch	mm	inch					
141851122	22-300	0.9-12"	0-300	0-6"	0,01	±40	40	50	●
141851152	24-500	1-20"	0-500	0-20"		±60	60	60	●
141851162	30-600	1.2-24"	0-600	0-24"		±90	90	100	●



MICRON BORE DIGITAL CALIPER IP67

- Bore calipers for bore reading without removing the bar
- MICRON Swiss Digital IP67 electronics with PRESET function.
- **Calibration** certificate included (ISO17025 (Ilac MRA))

Item No	Range				Reso- lution	Accu- racy	Jaws		Preset
	Internal		External				Down	Depth	
	mm	inch	mm	inch					
141851126	22-300	0.9-12"	0-300	0-6"	0,001	±40	40	50	●
141851156	24-500	1-20"	0-500	0-20"		±60	60	60	●
141851166	30-600	1.2-24"	0-600	0-24"		±90	90	100	●



BORE COMPUTERIZED CALIPER

- Bore calipers for bore reading without removing the bar
- Computerized **MICS** indication system Modification with **Long range** Wireless, Wireless HID or USB HID data transfer to Windows, Android, iOS, macOS, Linux systems direct to any app.
- **Calibration** certificate included (ISO17025 (Ilac MRA))



Item No	Range				Reso- lution	Accu- racy	Jaws		Constant Force	Measuring HUB	Analog scale	Graphic	Preset	Go/NoGo	Max/Min	Formula	Timer	Temp comp	Linear corr	Calibr date	Recharge	Memory	WIRELESS	USB
	Internal		External				Down	Depth																
	mm	inch	mm	inch			mm	mm																
141851127	22-300	0.9-12"	0-300	0-6"	0,01	±30	40	50	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
141851157	24-500	1-20"	0-500	0-20"		±40	60	60	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
141851167	30-600	1.2-24"	0-600	0-24"		±70	90	100	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•


- Bore calipers for bore reading without removing the bar
- CONSTANT Force module for high accuracy and repeatability
- Computerized **MICS** indication system Modification with **Long range** Wireless, Wireless HID or USB HID data transfer to Windows, Android, iOS, macOS, Linux systems direct to any app.
- **Calibration** certificate included (ISO17025 (Ilac MRA))



PAT.US10184772 PAT.UA152320

Item No	Range		Reso- lution	Accu- racy	Jaws			Max bore D	Roll system	Constant Force	Measuring HUB	Analog scale	Graphic	Preset	Go/NoGo	Max/Min	Formula	Timer	Temp comp	Linear corr	Calibr date	Recharge	Memory	WIRELESS	USB
	Internal				Down	Depth	Anvil D																		
	mm	inch																							
141851037	20-300	0.9-12"	0,01	±20	100	60	10	180	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
141851057	30-500	1-20"		±35	150	100	14	270	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
141851107	50-1000	2-40"		±40	150	100	14	270	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
141851157	1000-1500	40-60"		±45	200	150	18	370	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
141851207	1500-2000	60-80"		±55	250	150	18	460	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
141851257	2000-2500	80-100"		±60	300	200	26	550	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Folders / 2000 val																							Long range / HID	USB HID / Update	

OPTIONAL ACCESSORIES



DOWNLOAD APP

