


UNIVERSAL CALIPER

- Patent US 10184772, UA104879, UA99687, UA128692, US126928 by MICROTECH
- 3 types of measurings jaws in set (point, neck, centerline) for internal, external and centerline measuring
- Digital or Wireless or Computerized **MICS** indication system with 1, 5 or 10 micron resolution
- Modification with **Wireless** data transfer to Windows, Android, iOS applications with distance up to **50 m**
- Modification with self lubrication patented technology (Pat. UA121314 by MICROTECH)
- **FREE** version of software for Windows PC, Android, iOS tablets and smartphones
- Calibration certificate included (ISO17025 (Ilac MRA))



max 30 m
data transfer distance



max 50 m
data transfer distance



UNIVERSAL DIGITAL CALIPER IP54

Item No	Range		Resolution		Accuracy	B*	Protection class	Digit height	Calibration	
	mm	inch	mm	inch	μm	mm		mm		
141630155	0-150	0-6"	0,005	0.0002"	± 30	30	IP54	9	+	
141630205	0-200	0-8"			± 30	50		IP54		9
141630305	0-300	0-12"			± 30					9

UNIVERSAL DIGITAL CALIPER IP67

Item No	Range		Resolution		Accuracy	B*	Lubrication system	Protection class	Preset function	Digit height	Data output	Calibration
	mm	inch	mm	inch	μm	mm				mm	Wireless	
141630153	0-150	0-6"	0,01	0.0005"	± 30	30	+	IP67	+	11,5	-	+
141631154					± 30	+	IP67	+	11,5	max 30m	+	
141630203	0-200	0-8"			± 30	50	+	IP67	+	11,5	-	+
141631204					± 30		+	IP67	+	11,5	max 30m	+
141630303	0-300	0-12"			± 30	+	IP67	+	11,5	-	+	
141631304					± 30	+	IP67	+	11,5	max 30m	+	

UNIVERSAL MICRON COMPUTERIZED CALIPER WIRELESS

Item No	Range		Resolution		Accuracy	B*	Protection class	External Force	Indication	Data output	Calibration
	mm	inch	mm	inch	μm	mm		N	Wireless		
141630157	0-150	0-6"	0,005	0.0002"	± 20	30	IP54	8	computerized MICS system with 1,54" touchscreen	max 50 m	+
141630158			0,001	0.00005"	± 15		IP54	8		max 50 m	+
141630207	0-200	0-8"	0,005	0.0002"	± 25	50	IP54	8		max 50 m	+
141630208			0,001	0.00005"	± 15		IP54	8		max 50 m	+
141630307	0-300	0-12"	0,005	0.0002"	± 25	50	IP54	8		max 50 m	+
141630308			0,001	0.00005"	± 20		IP54	8		max 50 m	+

DIMENSIONAL DRAWING

