


TUBE CALIPER

- Patent US 10184772, UA104879, UA99687, UA128692, US126928 by MICROTECH
- For tube thickness measurements
- Digital or Wireless or Computerized **MICS** indication system with 1, 5 or 10 micron resolution
- Modification with **Wireless** data transfer to Windows, Android, iOS applications with distance up to **50 m**
- Modification with self lubrication patented technology (Pat. UA121314 by MICROTECH)
- **FREE** version of software for Windows PC, Android, iOS tablets and smartphones
- Calibration certificate included (ISO17025 (Ilac MRA))



max 30 m
data transfer distance



LUBRICATION SYSTEM

max 50 m
data transfer distance



1µm



TUBE DIGITAL CALIPER IP54

Item No	Range		Resolution		Accuracy	Dimensions			Waterproof	Digit height	Calibration
	mm	inch	mm	inch		A	B	C			
	mm	inch	mm	inch	μm	mm	mm	mm		mm	ISO 17025
141230155	0-150	0-6"	0,005	0.0002"	± 30	46	30	4	IP54	9	+
141230205	0-200	0-8"			± 30	50	40	4	IP54	9	+
141230305	0-300	0-12"			± 30	50	40	4	IP54	9	+

TUBE DIGITAL CALIPER IP67

Item No	Range		Resolution		Accuracy	Dimensions			Lubrication system	Waterproof	Digit height	Data output	Calibration
	mm	inch	mm	inch		A	B	C					
	mm	inch	mm	inch	μm	mm	mm	mm			mm	Wireless	ISO 17025
141230153	0-150	0-6"	0,01	0.0005"	± 30	46	30	4	+	IP67	11,5	-	+
141231154					± 30	46	30	4	+	IP67	11,5	max 30m	+
141230203	0-200	0-8"			± 30	50	40	4	+	IP67	11,5	-	+
141231204					± 30	50	40	4	+	IP67	11,5	max 30m	+
141230303					± 30	50	40	4	+	IP67	11,5	-	+
141231304	0-300	0-12"			± 30	50	40	4	+	IP67	11,5	max 30m	+

TUBE MICRON COMPUTERIZED CALIPER WIRELESS

Item No	Range		Resolution		Accuracy	Dimensions			Waterproof	Indication	Data output	Calibration
	mm	inch	mm	inch		A	B	C				
	mm	inch	mm	inch	μm	mm	mm	mm			Wireless	ISO 17025
141230157	0-150	0-6"	0,005	0.0002"	± 20	46	30	4	IP54	computerized MICS system with 1,54" touchscreen	max 50 m	+
141230158			0,001	0.00005"	± 20	46	30	4	IP54		max 50 m	+
141230207	0-200	0-8"	0,005	0.0002"	± 25	50	40	4	IP54		max 50 m	+
141230208			0,001	0.00005"	± 25	50	40	4	IP54		max 50 m	+
141230307			0-300	0-12"	0,005	0.0002"	± 25	50	40		4	IP54
141230308	0,001	0.00005"			± 25	50	40	4	IP54		max 50 m	+

SPECIAL DIAMETER ANVILS FOR CUSTOMERS REQUEST

DIMENSIONAL DRAWING

