


- Industry 4.0 adopted sub-micron Computerized thickness gauge for soft materials
- Functions: Go/NoGo, Max/Min, Formula, Timer, Linear correction, Temperature correction, Resolution selecting, Connection status
- Memory manager: 2000 values, Folders system, Statistics mode, Memory data transfer
- Quick reading system (50 value/sec)
- **4 MODES DATA TRANSFER:** WIRELESS to MDS app (Windows, Android, iOS, MacOS); WIRELESS HID, WIRELESS HID+MAC, USB HID
- Calibration certificate included (ISO17025 (Ilac MRA))



CUSTOM RANGE AND DEPTH FOR REQUEST

Item No	Standard	Material	Range	Resol.	Depth	Accuracy	Base	Measuring surface		Force		Timer auto
			mm	mm	mm	mm	mm	mm	cm ²	N	kPA	sec.
137331231	ASTM D5199-01-B	geomembranes	0-10	0,0001	50	0,02	D6,35	D6,35	0,3167	0,633±0,006	20±0,2	5
137331232	ASTM D5199-01-A	geotextiles, geonets, geocomposite drainage materials				0,02	D76,4	D56,4	25	5±0,05	2±0,02	5
137331233	ISO 2286-3	rubber, plastic coated fabrics				0,02	D60	D10	0,785	1,88±1,9	24±2,4	30
137331234	ISO 2589	leather				0,015	D16 / D50	D10	0,785	3,85±0,1	49,1	5
137331235	ISO 5084-0	textiles				0,01-0,02	D100	D50,5	20	2±0,02	1±0,01	30
137331236	ISO 5084-A3	textiles				0,01-0,02	D100	D50,5	20	5±0,05	1±0,01	30
137331237	ISO 9863-1-C	polymeric and bituminous geosynthetic barriers				0,02	D56,4	D56,4	25	50±0,5	20±02	5
137331238	ISO 9863-1	polymeric and bituminous geosynthetic of non-inifrom thickness				0,015	R 1	R 1	25	0,6±0,1		5

OPTIONAL ACCESSORIES



DOWNLOAD APP

