

- Industry 4.0 adopted Intelligent depth caliper with computerized MICS system (Patents US10184772, UA174949, UA126928)
- **ENERGY ECONOMY** 2.13" E-ink display (200+ working hours / 1 charging)
- **Functions:** Go/NoGo, Max/Min, Formula, Timer, Linear correction, Resolution selecting, Connection indication
- **Memory manager:** 1000 values, Statistics mode, Memory data transfer
- **4 MODES DATA TRANSFER:** WIRELESS to MDS app (Windows, Android, iOS, MacOS); WIRELESS HID, WIRELESS HID+MAC, USB HID
- Calibration certificate included (ISO17025 (Ilac MRA))



Item No	Range		Reso- lution	Accu- racy	Base	Preset	Go/NoGo	Max/Min	Formula	Timer	Temp comp	Linear corr	Calibr date	Recharge	Memory	WIRELESS	USB
	mm	inch															
1432010158	0-150	0-6"	0,005	±15	102	•	•	•	•	•	•	•	•	•	1000 val	•	•
1432010208	0-200	0-8"		±20		•	•	•	•	•	•	•	•	•		•	•
1432010308	0-300	0-12"	0,01	±25	150	•	•	•	•	•	•	•	•	•	Folders / 2000 val	•	•
				±40		•	•	•	•	•	•	•	•	•		•	•
			±50	•	•	•	•	•	•	•	•	•	•	•	USB HID / Update	•	•
			±70	•	•	•	•	•	•	•	•	•	•	•		•	•
			±90	•	•	•	•	•	•	•	•	•	•	•	•	•	•

## COMPUTERIZED DEPTH CALIPER

- Industry 4.0 adopted depth caliper with computerized MICS system (Patents US10184772, UA174949, UA126928)
- **Functions:** Go/NoGo, Max/Min, Formula, Timer, Linear correction, Temperature correction, Resolution select, Connection indication
- **Memory manager:** 2000 values, Folders system, Statistics mode, Memory data transfer
- **E-Force control module** with Force selection 1-20N, color indication, AUTO-Force mode, Force indication
- **4 MODES DATA TRANSFER:** WIRELESS to MDS app (Windows, Android, iOS, MacOS); WIRELESS HID, WIRELESS HID+MAC, USB HID
- Calibration certificate included (ISO17025 (Ilac MRA))



Item No	Range		Reso- lution	Accu- racy	Base	Preset	Go/NoGo	Max/Min	Formula	Timer	Temp comp	Linear corr	Calibr date	Recharge	Memory	WIRELESS	USB
	mm	inch															
1432010157	0-150	0-6"	0,005	±15	102	•	•	•	•	•	•	•	•	•	Folders / 2000 val	•	•
1432010207	0-200	0-8"		±20		•	•	•	•	•	•	•	•	•		•	•
1432010307	0-300	0-12"	0,01	±25	150	•	•	•	•	•	•	•	•	•	Long range / HID	•	•
1432010507	0-500	0-20"		±40		•	•	•	•	•	•	•	•	•		•	•
1432011007	0-1000	0-40"	0,01	±50	150	•	•	•	•	•	•	•	•	•	USB HID / Update	•	•
1432012007	0-2000	0-40"		±70		•	•	•	•	•	•	•	•	•		•	•
1432013007	0-3000	0-40"	0,01	±90	150	•	•	•	•	•	•	•	•	•	•	•	•
				±90		•	•	•	•	•	•	•	•	•	•	•	•

DOWNLOAD APP

